

HOT DOG HUTCH SIDE PANEL REPLACEMENT KIT (P/N 7001215)

TOOLS: Flat head and Phillips head screwdrivers

AFFECTED PRODUCTS: HDH-3DR Units

PARTS INCLUDED:

- 2 - Front/Back Panel (P/N 0508075)
- 1 - Adhesive/Sealant - RTV 3oz (P/N 2140154)
- 4 - Machine Screw #8-32 (P/N 3080203)
- 1 - Instruction Sheet (P/N 1011402)

Instructions

1. Remove all food product from the unit.
2. Turn the Thermostat Knob fully counterclockwise to the off position. Turn the Rocker Switch to OFF.
3. Unplug the power cord and allow the unit to cool before proceeding.
4. Remove the unit from Cafe Area.
5. Remove the Top Cover and all accessories from inside the unit. Set these items aside.
6. Place a bucket under the Drain Cap. Remove the Drain Cap and allow the water to drain from the unit.
7. Using a Phillips head screwdriver, remove the two screws from the upper left and right of both side panels.

8. Remove the existing side panels. You may need to rock the panels back and forth to loosen the existing sealant.



9. Use a flat head screwdriver to remove all sealant residue and debris from the areas indicated in the image below. Clean the same areas with a clean, damp cloth so they are free of debris and sealant.



HOT DOG HUTCH SIDE PANEL REPLACEMENT KIT (P/N 7001215)

- Using the provided sealant, add sealant to the areas shown in the image below. This includes the INSIDE area of the vertical supports (left and right) and inside the horizontal channel. Apply the sealant evenly and be sure to follow all directions and precautions on the sealant packaging.



- Install the new side panels against the INSIDE of the vertical supports and inside the horizontal channel. See the figure below. Apply pressure to the side panels to create a tight bond between the sealant and panels. Secure the side panels with the provided screws.



- With the new side panels in place, apply sealant to the vertical and horizontal edges of the panels facing the OUTSIDE of the unit. This creates a water-tight seal.
- Wipe away any excess sealant.
- Allow the sealant to cure for 24 hours. Do not use the unit during this time. Do not add water to the unit during this time. Leave the top cover and accessories off the unit during this time.
- After the 24 hour curing period, install the accessories and return the unit to use.