






Muffin Toaster Best Practices

Model MT-12 & HEMT-12


DAILY

1. Remove spatula, crumb tray, and plate.
2. Wipe plate with a clean towel.
3. Use grill cleaner to clear any buildup from plate.
4. Wipe crumb tray and spatula with a clean towel.
5. Flip plate and replace in unit. Then replace crumb tray and spatula.



MONTHLY

1. Place a full load of 6 muffins (12 halves) into toaster.
2. Time a full-run toast cycle. It should last between 90 and 130 seconds (50 and 70 seconds for the HEMT-12).
3. Remove the muffins from toaster.
4. Adjust the upper timer setting if needed with a flathead screwdriver (clockwise to increase time, counterclockwise to decrease time).
5. Repeat steps 1 through 4 as needed until the full-run toast cycle lasts between 90 and 130 seconds. (50 and 70 seconds for the HEMT-12).



Muffin Toaster Best Practices

Model MT-12 & HEMT-12

6. Place a half-load of 3 muffins (6 halves) into toaster.



7. Time a partial-run toast cycle. It should last between 85 and 125 seconds (50 and 55 seconds for the HEMT-12).



8. Remove the muffins from toaster.



9. Adjust the lower timer setting if needed with a flathead screwdriver (clockwise to increase time, counterclockwise to decrease time).



10. Repeat steps 6 through 9 as needed until the partial-run toast cycle lasts between 85 and 125 seconds (50 and 55 seconds for the HEMT-12).



For additional information, refer to the appropriate Preventative Maintenance Card for your unit.