



ITEM	PART NO	DESCRIPTION	QTY.
1	0013963	MAIN ASSEMBLY	1
2	0400138	CONDUIT LOCKNUT 1/2"	1
3	0400315	STRAIN RELIEF-CORD CONNECTOR	1
4	0508787	BRACKET, TRAY	1
5	0701089	POWER CORD 230V IEC-309	1
6	1013017	OWNERS MANUAL ESM-600	1
7	1031458	SPEC LABEL, # 9300651	1
8	1200922	ASSEMBLY / TEST PROCEDUR	1
9	1250791	BOX, CARTON	1
10	1260524	FOAM INSERT, TOP-FRONT	1
11	1260525	FOAM INSERT, BTM-FRONT	1
12	1260526	FOAM INSERT, TOP-BACK	1
13	1260527	FOAM INSERT, BTM-BACK	1
14	2180270	SCRAP TRAY	1
15	5126003	POLYBAG-CLEAR (33 GAL)	1
16	5126009	POLYBAG (9" X 12") 2MIL	1
17	2130113	TURNER, LG BLACK	1
18	2130114	BRUSH, 1.5" W NYLON	1
19	2130190	SCRAPER, MES/ES	1
20	2180111	PLASTIC DISPENSING BOTTLE 16 OZ	1

NOTES:  
 1. PART NO. 1013017 SHOULD BE PLACED INSIDE POLYBAG #5126009 BEFORE BEING PLACED INTO CARTON BOX.

REV	DATE	PCO NO.	DESCRIPTION	BY
D	9/7/2023	PC101916	PN 1250791 WAS 1250294	RF
C	10/31/22	PC101431	RESTRUCTURED BOM FOR SINGLE LEVEL ASSEMBLY	JRP
B	2/4/19	PC-15390	B1 ADDED P/N 7001894; REMOVED P/N'S 0013662 & 0022899	KR
A	08/21/18	PC-13554	INITIAL RELEASE	DIP

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF A.J. ANTUNES & CO. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED HEREIN MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF A.J. ANTUNES & CO.

UNLESS OTHERWISE SPECIFIED:  
 INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5-2009  
 ALL DIMENSIONS: INCH [mm]  
 TOLERANCES:  
 FRACTIONS ±1/32" [.8mm]  
 DECIMAL  
 .xx ±.01" [.25mm]  
 .xxx ±.005" [.125mm]  
 ANGULAR: ±1°  
 NO BURRS ALLOWED  
 BREAK ALL SHARP CORNERS

DRAWN BY: D PATEL  
 DATE: 3/23/2018  
 APVD BY:  
 DATE:  
 PART DESCRIPTION:  
 ESM-600, 230V 50/60HZ EURO UNIT/HARMZD/IEC-309  
 MATERIAL SPECIFICATION:  
 SIZE: B  
 SCALE: 1:8  
 PART NUMBER: 9300651



THIRD ANGLE PROJECTION  
 DO NOT SCALE DRAWING

SHEET 1 OF 1  
 REV: D