

# **Vertical Contact Toaster | VCT-2000**



The Vertical Contact Toaster VCT-2000 is a staple in foodservice operations with a reputation for quality, performance and reliability around the world.

The Vertical Contact Toaster gives buns a consistent, golden brown finish which helps the sandwich stay firm and delicious. Additional products for the unit include a wide mouth bun feeder, motorized butter wheel, heated base, and back plate. The VCT-2000 features a digital controller for making precise adjustments to the quality of the toast for different bread products.



VCT-2000 Vertical Contact Toaster



### **Dual-Sided Platen**

Vertical Contact Toaster has more capacity than conventional single-sided toasters, allowing operators to quickly serve fresh products



#### **Minimal Bun Marking**

Forget burnt buns. Our belt wraps minimize marking of the buns for perfect a golden finish.




#### **Small Footprint**

The upright design saves valuable counter space, allowing it to easily integrate into any operation





# **Vertical Contact Toaster** | VCT-2000



### **Features:**

- · Auxiliary heater warms top side of buns
- · Space-saving vertical design
- · Continuously moving conveyor for immediate toasting
- Separate compression adjustments for the heel and the crown
- Release sheets allow buns to move easily down the heated platen without sticking or slipping
- Easy to operate and clean
- Stainless steel construction
- Available toasting times range from 10 to 28 seconds
- Additional products available: wide mouth bun feeder, butter wheel and heated base

| VCT-2000            |                       | Electrical Ratings |         |             |           | Dimensions |       |                     |                     |                     |                      |
|---------------------|-----------------------|--------------------|---------|-------------|-----------|------------|-------|---------------------|---------------------|---------------------|----------------------|
| Model &<br>Mfg. No. | Capacity*             | Approvals          | Plug    | Volts       | Watts     | Amps       | Hz.   | Width (A)           | Depth (B)           | Height (C)          | Shipping<br>Weight   |
| VCT-2000<br>9210200 | 10-sec.<br>toast time | ⊕ (€               | CEE 7/7 | 220<br>-240 | 3019-3593 | 13.7-15    | 50/60 | 22 1/4"<br>(565 mm) | 10 3/4"<br>(273 mm) | 23 1/4"<br>(591 mm) | 88 lbs.<br>(39.9 kg) |



VCT-2000

#### VCT-2000 (with wide mouth)

| Model &<br>Mfg. No. | Capacity*             | Approvals | Plug    | Volts       | Watts         | Amps    | Hz. | Width (A)           | Depth (B)           | Height (C)           | Shipping<br>Weight   |
|---------------------|-----------------------|-----------|---------|-------------|---------------|---------|-----|---------------------|---------------------|----------------------|----------------------|
| VCT-2000<br>9210212 | 10-sec.<br>toast time | ⊕ (€      | CEE 7/7 | 220-<br>240 | 3019-<br>3593 | 13.7-15 | 50  | 22 1/4"<br>(565 mm) | 10 3/4"<br>(273 mm) | 23 7/32"<br>(590 mm) | 88 lbs.<br>(39.9 kg) |
| VCT-2000<br>9210223 | 23-sec.<br>toast time | ₾ (€      | CEE 7/7 | 220-<br>240 | 3019-<br>3593 | 13.7-15 | 50  | 21 1/4"<br>(540 mm) | 15 1/4"<br>(387 mm) | 23 1/4"<br>(591 mm)  | 88 lbs.<br>(39.9 kg) |



VCT-2000 with Wide Mouth

\*Toast time will vary 20% depending on power frequency